

XADO gel-revitalizant for automatic transmission

Designed for restoring repair and protection from wear of automatic transmissions.

During the revitalization of automatic transmissions a cermet layer, grown on the crystal lattice of the metal surface layer, is formed on the friction pair surfaces (gears, bearings, hydraulic distributors, torque converter clutches). Thus the usual "metal to metal" pair is replaced by a practically non-wearing "cermet to cermet" pair.

Advantages

- Restores and protects friction metal parts from wear.
- Removes surface defects.
- Improves reliability of the mechanism operation and prolongs its life span.
- Reduces noise and vibration.
- Damps extreme loads.
- Protects parts against wear in case of low oil level.

Application instructions

1. Shake the can.
2. Spray the necessary quantity of gel-revitalizant into the oil filler neck (vent of the oil gage rod) of the automatic transmission.
3. Run the car as usual.
4. Revitalization is complete after 50 hours of mechanism operation (after 1,500 km run).

Note

The sure sign of revitalization process beginning is an improvement in automatic transmission operation (noise reduction and smoother gear shifting) as early as the first kilometers of after-application operation.

XADO revitalizant is compatible with all types of fluids for automatic transmissions: Dexron®, Mercon®, Mopar ATF®, CVT. It does not have chemical reaction with them and does not change their viscosity, friction and other physical-chemical characteristics.


10 ml

Art. XA 10615

Aerosol can in a shaped blister package


10 ml

Art. XA 10515

aerosol can

Dosage

Oil system capacity (L)	5–8	9–12	13–15
Quantity of cans (pcs)	1	2	3
Treatment scheme	once		